

## Landing Gear

 <div style="text-align: center;">  <p><b>28110U</b> Universal Landing Gear</p> <ul style="list-style-type: none"> <li>• 50,000 lb. capacity.</li> <li>• Crank Handle and Connecting Shaft Included with Ordered Pairs.</li> <li>• Warrantied against manufacturing defects for five (5) years.</li> </ul> <p><b>Lift Capacity: 50,000 lbs.</b></p> </div>	 <div style="text-align: center;">  <p><b>29110U</b> Universal Landing Gear</p> <ul style="list-style-type: none"> <li>• 66,000 lb. capacity.</li> <li>• Crank Handle and Connecting Shaft Included with Ordered Pairs.</li> <li>• Warrantied against manufacturing defects for five (5) years.</li> </ul> <p><b>Load Capacity: 66,000 lbs.</b></p> </div>																								
 <div style="text-align: center;">  <p><b>Binkley 50000 series</b></p> <p>Landing Gear Capabilities Lifting Capacity – Rated 100 ft. lbs. Input Torque 60,000 lbs. Ultimate Load Capacity 170,000 lbs. Side Load Capacity 29,000 lbs. Gear Ratio vs. Turns Per Inch Low Gear 34.4 High Gear 4.5</p> <p>Exclusive floating nut design for high side-load capacity and reduced dock-walk damage.</p> <p><b>LG-5001-70 Sand Shoe Set</b> <b>LG-5006-70 Cushion Foot Set (13" Round Foot)</b></p> </div>	 <div style="text-align: center;">  <p><b>Binkley 51000 series</b></p> <p>Landing Gear Capabilities Lifting Capacity – Rated 100 ft. lbs. Input Torque 50,000 lbs. Ultimate Load Capacity 140,000 lbs. Side Load Capacity 27,000 lbs. Gear Ratio vs. Turns Per Inch Low Gear 34.4 High Gear 4.5</p> <p><b>LG-4001-70 Sand Shoe Set</b> <b>LG-400E-70 Cushion Foot Set (13" Round Foot)</b></p> </div>																								
 <div style="text-align: center;">  <p><b>A400 series</b></p> <p><b>Load Capacities per pair</b> Lifting Capacity . . . . . 50,000 lbs. <i>at 100 ft. lbs. input torque</i> Static Load Capacity . . . . . 160,000 lbs. Side Load Capacity . . . . . 29,000 lbs.</p> <p><b>Gear Ratio</b> Low Gear . . . . . 32 Turns = 1" Travel High Gear . . . . . 3.5 Turns = 1" Travel</p> <p><b>A400T17 Outside Mount (Sand Shoe)</b> <b>A400G17 Outside Mount (10"x10" Cushion Foot)</b> <b>A401T17 Inside Mount (Sand Shoe)</b> <b>A401G17 Inside Mount (10"x10" Cushion Foot)</b></p> </div>	<div style="text-align: center;"> <h3>Landing Gear Accessories</h3> <p><b>Crank Handles</b> 7 1/2" Vertical 03-207-V &amp; H* 11 1/2" Vertical 03-211-V &amp; H* 15" Vertical 03-215-V 21" Vertical 03-221-V (* - Also available in Horizontal)</p> <table border="0"> <tr> <td></td> <td><b>Sand Shoes</b></td> <td><b>Sand Shoe Axle</b></td> <td></td> </tr> <tr> <td></td> <td>Hi Pro 05-300</td> <td>05-410</td> <td></td> </tr> <tr> <td></td> <td>Lo Pro 05-310</td> <td></td> <td></td> </tr> </table> <table border="0"> <tr> <td></td> <td><b>Axle Housing</b></td> <td><b>Adjustable Leg Brace</b></td> <td></td> </tr> <tr> <td></td> <td>06-345</td> <td>UT-26-41 26" to 41"</td> <td></td> </tr> <tr> <td></td> <td></td> <td>UT-58-72 58" to 72"</td> <td></td> </tr> </table> </div>		<b>Sand Shoes</b>	<b>Sand Shoe Axle</b>			Hi Pro 05-300	05-410			Lo Pro 05-310				<b>Axle Housing</b>	<b>Adjustable Leg Brace</b>			06-345	UT-26-41 26" to 41"				UT-58-72 58" to 72"	
	<b>Sand Shoes</b>	<b>Sand Shoe Axle</b>																							
	Hi Pro 05-300	05-410																							
	Lo Pro 05-310																								
	<b>Axle Housing</b>	<b>Adjustable Leg Brace</b>																							
	06-345	UT-26-41 26" to 41"																							
		UT-58-72 58" to 72"																							